


Product name	192F G657A1 MicroDuct cable MLT Black PA OD 8.0mm 4km/d
Product code	1083058
Product type	QXXE 192X9/125 G657A1
GTIN	7070701384009
ETIM-Class	EC000034



PRODUCT SPECIFICATIONS

Micro cables typically used in outdoor microduct installation applications. The cables are suitable for air-blown installation. Cable parameters such as cable diameter, stiffness and sheath friction are optimized for best installation performance. The cable is based on a multi loose tube construction with SZ design around a central strength member of fiberglass-reinforced plastic (FRP) which facilitates mid-span access.

Measurements

Length	1000 mm
Height	8 mm
Width	8 mm
Weight	59 g

Physical Characteristics

Fibre Count	192
Cable Construction	Multi Loose Tube (MLT)
Fibre Type	ITU-T G.657 A1
Fibres per Tube	24
Fibre Colour Sequence	EIA/TIA-598A
Tube Size	2 mm
Central Strength Member	FRP
No of Tubes	8
Tube Colour Sequence	EIA/TIA-598A

Outer Sheath Material	PA (Polyamid)
Colour of Cable Sheath	Black
Nominal Sheath Thickness	0,3 mm
No of Ripcords Below Outer Sheath	1
Cable Diameter	8 mm
Cable Diameter Tolerance	+/- 0.3 mm
Nominal Cable Weight	59 kg/km

Mechanical & Environmental Characteristics

Halogen Free	Yes
UV Proof	Yes
Metal free	Yes
Tensile Strength (N) IEC-60794-1-21-E1	1000 N
Crush Resistance - IEC- 60794-1-21-E3	500 N/10cm
Impact Strength (Nm) IEC-60794-1-21-E4	50
Torsion IEC-60794-1-21-E7	± 180°
Min. Bend Radius (During Installation) IEC-60794-1-21-E11	20 x d
Min. Bend Radius (After Installation) IEC-60794-1-21-E11	10 x d
Water Penetration Test IEC-60794-1-22-F5	1m head, 3m samples, 24 hrs.
Drip Test IEC-60794-1-21-E14	30 cm, 70°C, 24 hr
Temperature Performance Installation IEC-60794-1-22-F1	-15°C till +50°C
Temperature Performance Operation IEC-60794-1-22-F1	-40°C til +70°C
Temperature Performance Storage IEC-60794-1-22-F1	-40°C til +70°C