M E L B Y E

Product name	Ultima connect access chamber 750×750×900mm
Product code	2821809
GTIN	7070701364520
ETIM-Class	EC004532

Measurements

Length	885 mm
Height	900 mm
Width	885 mm
Weight	116 640 g

Technical Specifications - Chambers

Product group	Chamber module
Material	Glass Reinforced Polyester (GRP)
Material Color	Gray
Tensile Strength (ISO 527)	45 MPA
Flexural Modulus (ISO 14125)	9,5 GPA
Density (ISO 1183-1)	1,78 g/cm³
Service Temperature	-40 to 110°c
Surface Resistivity	1,00e+14 ohm
Volume Resistivity	1e+12 ohm/cm
Fire Performance (UL94)	hb rating
Heat deflection temperature (ISO 75-2)	200 °C
Water Absorption (Non polar polymer) (ISO 62)	0,5
Limited Oxygen Index (ISO 4589)	23
Vertical loads EN124	F900
External Length	885 mm
External Width	885 mm

M E L B Y E

Melbye Group | Fordonsvägen 17 | SE-553 02 Jönköping | Tlf +46 36 332 07 00 | info@melbye.se | www.melbye.se

Melbye Group - Region Danmark | Fordonsvägen 17 | DK-553 02 Jönköping | Tlf +45 57 60 09 60 | melbye@melbye.as | www.melbye.as

Melbye Group | Prost Stabels vei 22 | Postboks 160 | NO-2019 Skedsmokorset | Tlf +47 63 87 01 50 | ms@melbye.no | www.melbye.no

Melbye Ltd |The Technology Centre Station Road, Framlingham Woodbridge, IP13 9EZ United Kingdom | +44 (0)7903 288561 | te@melbye.se | melbyefibre.com

03/09/2026

External Hight	900 mm
Internal Length	750 mm
Internal Width	750 mm
Internal Hight	900 mm

Sustainability

product.sustainability-label.epd	Yes