

Product name	Ultima connect access chamber 750×750×1050mm
Product code	2821810
GTIN	7070701364537
ETIM-Class	EC004532



Measurements

Length	885 mm
Height	1 050 mm
Width	885 mm
Weight	136 080 g

Technical Specifications - Chambers

Product group	Chamber section
Material	Glass Reinforced Polyester (GRP)
Material Color	Gray
Tensile Strength (ISO 527)	45 MPA
Flexural Modulus (ISO 14125)	9,5 GPA
Impact Strength (ISO 179)	50 KJ/m ²
Density (ISO 1183-1)	1,78 g/cm ³
Service Temperature	-40 to 110°C
Surface Resistivity	1,00e+14 ohm
Volume Resistivity	1e+12 ohm/cm
Fire Performance (UL94)	hb rating
Heat deflection temperature (ISO 75-2)	200 °C
Water Absorption (Non polar polymer) (ISO 62)	0,5 %
Limited Oxygen Index (ISO 4589)	23 %
Vertical loads EN124	F900
External Length	885 mm

External Width	885 mm
External Hight	1 050 mm
Internal Length	750 mm
Internal Width	750 mm
Internal Hight	1 050 mm

Sustainability

product.sustainability-label.epd	Yes
----------------------------------	-----