

<b>Product name</b>	Patch SM SPX 1xSC/APC-SC/APC G657A2 White 4mm LSZH 1m
<b>Product code</b>	
<b>GTIN</b>	
<b>ETIM-Class</b>	ECO01263



## PRODUCT SPECIFICATIONS

Fiberoptic patch cord singlemode G657A2 with white 4mm simplex cable and SC/APC-SC/APC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols.

## Measurements

<b>Length</b>	210 mm
<b>Height</b>	15 mm
<b>Width</b>	180 mm
<b>Weight</b>	20 g

## Technical Specifications - Connectors

<b>Max insertion loss per connector (APC)</b>	0,3 dB
<b>Max Optical Return Loss for APC connector</b>	-65 dB
<b>Radius of Curvature APC</b>	5-12
<b>Max Vertex Offset</b>	50 µm

## Technical Specifications - Patch Cords

<b>Fibre Type</b>	ITU-T G.657 A2
<b>Outer Sheath Material</b>	LSZH (Low Smoke Zero Halogen)
<b>Colour of Cable Sheath</b>	White
<b>Cable Diameter</b>	4 mm
<b>Temperature ranges for Operation</b>	-40°C to +85°C
<b>Temperature ranges for transport and storage</b>	-40°C to +85°C
<b>Halogen Free</b>	Yes