


Product name	Composite Suspension Insulator
Product code	2861123
Product type	145kV210-1572-20231028
GTIN	7070701376134
ETIM-Class	EC003514



Measurements

Length	1 572 mm
Height	140 mm
Width	140 mm
Weight	7 400 g

Insulator - Dimentions

Section Length	1 572 mm
Diameter	140 mm
Weight	7 400 g
Line fitting	Kulehake
Ground fitting	Kulebolt
Number of Sheds	49
Weathershed Spacing	24 mm
Core diameter	24 mm

Insulator - Mechanical data

Tensile Strength SML	210 kN
Working Load RTL	105 kN

Insulator - Electrical specifications

Voltage Level	145 kV
Power Frequency Wet Withstand 50Hz	270 kV
Arc Distance Dry	1 270 mm
Impulse Withstand Voltage Positive	650 kV
Leakage Distance	4 165 mm

Technical Specifications - Insulator

Insulation Material	HTV silikon
Standard	IEC 61109
Colour	Grå

Technical Specifications - High voltage insulator

Model	Other
Rated voltage	1 kV
Material	Other
Length	1 mm
Diameter	1 mm
Weight	1 kg
Creepage path	1 mm
Min. dry lightning impulse withstand voltage	1 kV
Wet power frequency withstand voltage	1 kV
Breaking load	1 kN
Pollution degree	3

Sustainability

product.sustainability-label.epd	Yes
----------------------------------	-----