

<b>Product name</b>	Line post insulator K-clamp 7,6-34mm
<b>Product code</b>	2861253
<b>Product type</b>	KL46SK
<b>GTIN</b>	7070701026329
<b>ETIM-Class</b>	EC003514



## Measurements

<b>Length</b>	540 mm
<b>Height</b>	160 mm
<b>Width</b>	155 mm
<b>Weight</b>	5 540 g

## Insulator - Dimentions

<b>Section Length</b>	500 mm
<b>Diameter</b>	159 mm
<b>Line fitting</b>	k-klemme
<b>Base Fitting</b>	bred
<b>Insulator bolt diameter tread</b>	unc 3/4"
<b>Overall Diameter Base Fitting</b>	102 mm
<b>Conductor Diameter</b>	7,6-34 mm
<b>Number of Sheds</b>	6
<b>Polymer length</b>	284 mm

## Insulator - Mechanical data

<b>Specified Cantilever Load SCL</b>	12,5 kN
<b>Reference Cantilever Load RCL</b>	6 kN

## Insulator - Electrical specifications

Power Frequency Wet Withstand 50Hz	100 kV
Arc Distance Dry	339 mm
Impulse Withstand Voltage Positive	225 kV
Withstand Voltage - Lightning Impuls	240 kV
Leakage Distance	860 mm

## Technical Specifications - Insulator

Insulation Material	silikon
Standard	61109
Colour	grå