

| | |
|---------------------|-------------------------------------|
| Product name | Arrester 440V For transformer term. |
| Product code | 2866136 |
| GTIN | 7070701373652 |
| ETIM-Class | EC002676 |



Measurements

| | |
|---------------|---------|
| Length | 385 mm |
| Height | 120 mm |
| Width | 155 mm |
| Weight | 1 200 g |

low voltage surge arrester - electrical specifications

| | |
|--|----------------------|
| Continuous Operating Voltage Uc (Vrms) | 440 V |
| Nominal discharge current 8/20μ In | 10 kA |
| Maximum discharge current 8/20μ In | 40 kA |
| voltage_protection_level_up | 1640 V |
| Up/Uc | 4 |
| For voltage system | 1000 V |
| Frequency | 48-62 Hz |
| Energy Absorption Capacity | 5kj/1000v uc |
| Short-circuit current withstand capability | 4,5 kA |
| Short time overvoltage | 1440v, 200ms |
| Temporary overvoltage | 400v, 5s |
| Surge class | ii |
| Standard | en 61643-11: 2013-06 |

Technical Specifications - Low voltage Surge arrester

| | |
|--------------------------------------|-----------------|
| Disconnecter | Yes |
| Surge Arrester Block Material | zno |
| Colour | sort/rød |
| Bracket Type | trafotilkopling |
| Bolt Type | m8 |