

<b>Product name</b>	Arrester 440V Base
<b>Product code</b>	2866138
<b>GTIN</b>	7070701373676
<b>ETIM-Class</b>	EC002676



## Measurements

<b>Length</b>	71 mm
<b>Height</b>	61 mm
<b>Width</b>	71 mm
<b>Weight</b>	180 g

## low voltage surge arrester - electrical specifications

<b>Continuous Operating Voltage <math>U_c</math> (Vrms)</b>	440 V
<b>Nominal discharge current 8/20<math>\mu</math> In</b>	10 kA
<b>Maximum discharge current 8/20<math>\mu</math> In</b>	40 kA
<b>voltage_protection_level_up</b>	1640 V
<b>Up/Uc</b>	4,0
<b>For voltage system</b>	1000 V
<b>Frequency</b>	48-62 Hz
<b>Energy Absorption Capacity</b>	5kj/1000v uc
<b>Short-circuit current withstand capability</b>	4,5 kA
<b>Short time overvoltage</b>	14405kj/1000v uc, 200ms
<b>Temporary overvoltage</b>	400v, 5s
<b>Surge class</b>	ii
<b>Standard</b>	61643-11: 2013-06

## Technical Specifications - Low voltage Surge arrester

<b>Disconnecter</b>	Yes
<b>Surge Arrester Block Material</b>	zno
<b>Colour</b>	sort/rød
<b>Bracket Type</b>	ingen
<b>Bolt Type</b>	m8