

<b>Product name</b>	KL-28S-V SILICONE POST TYPE
<b>Product code</b>	2861221
<b>Product type</b>	KL28SV
<b>GTIN</b>	7070701026145
<b>ETIM-Class</b>	EC003514



## Measurements

<b>Length</b>	350 mm
<b>Height</b>	160 mm
<b>Weight</b>	3 793 g

## Insulator - Dimentions

<b>Section Length</b>	368 mm
<b>Diameter</b>	132
<b>Line fitting</b>	vertikal topp
<b>Base Fitting</b>	bred for 3/4" unc isolatorbolt
<b>Insulator bolt diameter tread</b>	unc 3/4"
<b>Insulator Bolt Diameter</b>	24 mm
<b>Overall Diameter Base Fitting</b>	102 mm
<b>Number of Sheds</b>	4

## Insulator - Mechanical data

<b>Specified Cantilever Load SCL</b>	12,5 kN
<b>Reference Cantilever Load RCL</b>	5,5 kN

## Insulator - Electrical specifications

Voltage Level	24 kv
Power Frequency Wet Withstand 50Hz	75 kV
Arc Distance Dry	244 mm
Impulse Withstand Voltage Positive	170 kV
Withstand Voltage - Lightning Impuls	170 kV
Leakage Distance	439 mm

## Technical Specifications - Insulator

Insulation Material	silikon
Standard	iec61109
Colour	grå