

|                     |  |
|---------------------|--|
| <b>Product name</b> | Earthing lace with cable lugs 50 mm <sup>2</sup> 2.0 m |
| <b>Product code</b> | 2879043  |
| <b>Product type</b> | JL 50 2.0 M  |
| <b>GTIN</b>         | 7070701031217  |
| <b>ETIM-Class</b>   | EC002809   |



## Measurements

|               |        |
|---------------|--------|
| <b>Length</b> | 300 mm |
| <b>Height</b> | 30 mm  |
| <b>Width</b>  | 300 mm |
| <b>Weight</b> | 1152 g |

## Technical Specifications

|  |                    |
|--|--------------------|
| <b>Conductor Material</b>              | Kobber             |
| <b>Insulation Material</b>             | EPDM               |
| <b>Diameter Bolt Hole</b>              | 13 mm              |
| <b>Halogen Free</b>                    | Yes                |
| <b>Cross Section</b>                   | 50 mm <sup>2</sup> |
| <b>Diameter Excluded Insulation</b>    | 10 +/- 0,2 mm      |
| <b>Diameter Included Insulation</b>    | 13 +/- 0,4 mm      |
| <b>Composition / Number of Threads</b> | 1592x0,2           |
| <b>Rated Current Ik1 1 sec</b>         | 10 kA              |
| <b>Rated Current Ik1 0.5 sec</b>       | 14 kA              |
| <b>Standard</b>                        | IEC-61138          |