

<b>Product name</b>	Cable joint 1kV 3-4x16-50mm <sup>2</sup> heatshrink with connectors
<b>Product code</b>	1167418
<b>Product type</b>	MPC-3
<b>GTIN</b>	7070701008899
<b>ETIM-Class</b>	EC001169



## Measurements

<b>Length</b>	570 mm
<b>Height</b>	70 mm
<b>Width</b>	220 mm
<b>Weight</b>	382 g

## Technical Specifications - Joint 1kV

<b>Voltage</b>	1 kV
<b>Number of Conductors</b>	3
<b>Screen</b>	Yes
<b>Incl Contact Material</b>	Mechanical
<b>Incl. Liners</b>	No
<b>Insulation Type</b>	Heat Shrink Tube
<b>Halogen Free</b>	Yes

## Application

<b>Plastic Insulated Cables</b>	Yes
<b>Transition Joint</b>	No
<b>Installation Type</b>	Straight
<b>Type</b>	Heat Shrink

## Cable specifications for contact material

<b>Aluminum Stranded</b>	10-50 mm <sup>2</sup>
<b>Aluminum Sector Stranded</b>	35-50 mm <sup>2</sup>
<b>Aluminum Solid</b>	10-50 mm <sup>2</sup>
<b>Aluminum Sector Solid</b>	35-50 mm <sup>2</sup>
<b>Copper Stranded</b>	6-50 mm <sup>2</sup>
<b>Copper Sector Stranded</b>	35-50 mm <sup>2</sup>
<b>Copper Solid</b>	6-50 mm <sup>2</sup>
<b>Copper Class 5 multistranded</b>	6-50 mm <sup>2</sup>