

Product name	Arrester Station Low Ur 30kV mocw 24,4kV w/disconnector
Product code	2866119
Product type	214524C2CI
GTIN	7070701358505
ETIM-Class	EC002676



Measurements

Length	108 mm
Height	515 mm
Width	208 mm
Weight	7 700 g

Technical Specifications - Surge arrester

Length	548 mm
Type	214524-cc2ci
Wild Life Protection	Yes
Disconnecter	Yes
Surge Arrester Block Material	zno
Insulation Material	esp
Mounting Position	isoler brakket
Colour	mørk grå
Bracket Type	ingen
Bolt Type	m12

Surge Arresters - Electrical Specification

Continuous Operating Voltage (COV)	24,4 kV
Rated Voltage	30 kV

0.5µ Steep Front	93,4
Maximum Discharge Voltage kV / 1,5 kA	70,3 kV
Maximum Discharge Voltage kV / 3 kA	73,8 kV
Maximum Discharge Voltage 5 kA	77,3 kV
Maximum Discharge Voltage 10 kA	80,7 kV
Maximum Discharge Voltage 20 kA	90,6 kV
Maximum Discharge Voltage 40 kA	101,8 kV
Creep and Leakage Distance	1 173 mm
Maximum Switching Surge Protective Level @ 0,5 kA	65,3
Withstand Voltage - 50 Hz Wet	134 kV
Withstand Voltage - Lightning Impuls	204 kV
Withstand Voltage - Switching Impulse	63,5 kV
Pressure Relief Capability-Symmetrical rms	40 kA
Surge class	SL (Station Low)
Standard	iec 60099-4