

Product name	Arrester Station Low Ur 30kV mocw 24,4kV u/bracket
Product code	2866117
Product type	214524CCBE
GTIN	7070701358482
ETIM-Class	EC002676



Measurements

Length	108 mm
Height	515 mm
Width	108 mm
Weight	5 900 g

Technical Specifications - Surge arrester

Length	515 mm
Type	214524-ccbe
Wild Life Protection	No
Disconnecter	No
Surge Arrester Block Material	zno
Insulation Material	esp
Colour	mørk grå
Bracket Type	ingen
Bolt Type	m12

Surge Arresters - Electrical Specification

Continuous Operating Voltage (COV)	24,4 kV
Rated Voltage	30 kV
0.5µ Steep Front	93,4

Maximum Discharge Voltage kV / 1,5 kA	70,3 kV
Maximum Discharge Voltage kV / 3 kA	73.8 kV
Maximum Discharge Voltage 5 kA	77,3 kV
Maximum Discharge Voltage 10 kA	80,7 kV
Maximum Discharge Voltage 20 kA	90,6 kV
Maximum Discharge Voltage 40 kA	101,8 kV
Creep and Leakage Distance	1173 mm
Maximum Switching Surge Protective Level @ 0,5 kA	65,3
Withstand Voltage - 50 Hz Wet	134 kV
Withstand Voltage - Lightning Impuls	204 kV
Withstand Voltage - Switching Impulse	63,5 kV
Pressure Relief Capability-Symmetrical rms	40 kA
Surge class	SL (Station Low)
Standard	iec 60099-4